



ST-250 Signalling Torch



Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 12 key areas:

- Lifeiacket Lights
 - Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
 - Special LightsLED Flares
- Forward Looking Sonars (FLS)Bridge Navigational Watch
 - Alarm System (BNWAS)
 - Salinometers
 - Oil Level Alarm
- Electronic Inclinometer
 Agency for a range of world-renowned safety product brands
 - (supplied to the Danish market)

Further Information

For further information on our products, please see our website: www.daniamant.com

Introduction

Daniamant introduces the new ST-250 Signalling Torch for use in liferafts and lifeboats, plus other lifesaving situations.

Approved to ISO18813:2006 and SOLAS requirements the ST-250 Torch is capable of Morse signalling and a constant beam, producing a maximum concentrated beam of 250cd.

Lasting a minimum of 5 hours, the torch is supplied with a spare LED bulb and battery and enclosed in a moisture proof case.

In addition to this, the Torch has been tested to IP67 and IP68 and is waterproof to 50m. It is compact and lightweight and uses user replaceable AA alkaline cell's (lithium can also be used to increase the operating time further). Ideal for everyday cabin use as well as in emergency liferaft grab bags.

Features:

- Morse signalling
- Easy 'twist action' steady beam function
- User replaceable batteries
- User replaceable bulb
- CE mark
- Lanyard
- Moisture proof storage case
- Lightweight

Installation:

The torch is supplied in a storage box and is ready for immediate use.

Service & Maintanance:



Due to the torch using Alkaline batteries it is recommended to check the batteries once per year and replace if required.